



RWG500



Industrial Liner Rewinder



Universal, Reliable and Durable Rewinder



Auto-Adjust
Take-Up Speed



User-Friendly
Operation Panel



Up to 7 inch Wide
Label Support

Universal Printer Compatibility



GENERAL SPECIFICATIONS

MODEL		RWG500
OPERATION CHARACTERISTICS		
Environment	Operating	41° F – 104° F (5° C – 40° C), 30%-80% RH, non-condensing
	Storage	23° F – 140° F (-5° C – 60° C), 30%-90% RH, non-condensing
Regulatory Approvals		UL/C-UL, FCC, CE, TÜV
Dimensions		11" (280 mm) W x 12.6" (320 mm) D x 9" (230 mm) H
Weight		7.5 kg (16.5 lbs.) or less
Noise Level		Less than 60 dB
Input Power		EXT Cable Connection to SATO Printers (DC +24V, 2A)
Supported Printer Models		CL4NX Plus, CL6NX Plus, M84Pro, TG3, CL4NX, CL6NX, M5900Rve, CL408/412e, CL608/612e
REWINDING CHARACTERISTICS		
Speed		Up to 15"/sec (381 mm/sec)
Method		38.1 mm (1.5") Spindle / 76.2 mm (3") Paper Core
Direction		Face-Out/Face-In (Counterclockwise/Clockwise)
Monitoring		Automatic Control by Tension Arm Position
Outer Diameter/Roll		Maximum 265 mm (11")
Media Size	Width	Standard: 25 mm - 131 mm (0.98" - 5.16") Optional: Up to maximum 180 mm (7.09")
	Pitch	8 mm - 400 mm (0.31" - 15.75")
	Roll Size	Standard: 220 mm (8.66") max O.D. Optional: 254 mm (10") max O.D. (CLNX & CLNX Plus Series only)
CONFIGURATIONS*		
WWRW55300	RWG500 - 5" Wide Label Rewinder (requires SATO printer EXT port)	
WWGT05970	Media Width Expansion Kit (up to 7" wide) for RWG500	
11S000188	RWG500 with Media Rewind Expansion Kit to 7" Width	
11S000189	RWG500 External Power Supply (required for SATO printer without EXT port)	
11S000201	RWG500 5" Wide Rewinder w/110/220V Auto-Switching Power Supply (for SATO printers without EXT port, or other printer brands)	
3CF-RJP-6NX	RWG500 Joining Plate for printer with width over 131mm (5.16")	

*Please contact your local SATO office for stock availability.