



# WS4



DT Model



TT Model

Maximizing performance and investment for versatile desktop label applications.

## SATO, Beyond Expectations

SATO pursues World Standard desktop printer designed for various regional markets and vertical segments.

### Easy to Use

- Small Footprint Design
- High Speed Throughput (Max 6ips Print Speed)
- Easy Firmware Download via USB
- Toolless platen/head replacement (for DT model)
- 3 Color Status LED



### Flexible Label / Ribbon Capability

- 300m Ribbon Capability
- Face In/Face Out Label and Ribbon
- Adjustable Imark Sensor
- 0.5"/1" Ribbon Core
- 1"/1.5" Label Core



### Enhanced Connectivity

- Multiple Interfaces Onboard
- Optional Bluetooth
- IPv4/IPv6 Support
- Multiple Emulation support (SZPL, SEPL, SDPL, SIPL)



## GENERAL SPECIFICATIONS

PRINT SPECIFICATIONS		WS408TT	WS412TT	WS408DT	WS412DT
Printing Method		Thermal Transfer		Direct Thermal	
Print Mode		Continuous, Tear-off, Dispenser, Cutter			
Print Resolution		203 dpi (8 dots/mm)	300 dpi (12 dots/mm)	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
Max. Print Speed		6ips(152.4mm/sec)	4ips(101.6mm/sec)	6ips(152.4mm/sec)	4ips(101.6mm/sec)
Max. Print Area	Width, mm (inch)	104mm (4.09")			
	Length, mm (inch)	999mm (39.33")			
CPU		32Bit RISC CPU (600MHz)			
Printer Memory		128MB ROM, 128MB RAM			

## CONSUMABLES SPECIFICATIONS (Recommended to use printer supplies manufactured or certified by SATO)

Sensor Type		I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)			
Media Type		Roll (Continuous, Die-cut), Fan-fold, Tag, Ticket			
Label Shape	Roll Diameter	Max : 127 mm (5"), Max for External Media Stand: 203.2 mm (8")			
	Core Diameter	φ25.4mm(1.0"), φ38.1mm(1.5")			
	Wind Direction	Face-In/Face-Out, No Setting Change Required			
Label Thickness		0.06mm (0.002") ~ 0.19mm (0.007")			
Label Size	Continuous Mode	Length	10 ~ 996 mm (including liner 13 ~ 999 mm)	10 ~ 996 mm (including liner 13 ~ 999 mm)	
		Width	25.4 ~ 115 mm (including liner 28.4 ~ 118 mm)	25.4 ~ 115 mm (including liner 28.4 ~ 118 mm)	
	Tear-Off Mode	Length	25.4 ~ 996 mm (including liner 28.4 ~ 999 mm) DT Mode: 30 ~ 996 mm (including liner 33~999mm)	25.4 ~ 996 mm (including liner 28.4 ~ 999 mm)	
		Width	25.4 ~ 115 mm (including liner 28.4 ~ 118 mm)	25.4 ~ 115 mm (including liner 28.4 ~ 118 mm)	
	Dispenser Mode	Length	25.4 ~ 152.4 mm (including liner 28.4 ~ 155.4 mm) DT Mode: 35 ~ 152.4 mm (including liner 38~155.4mm)	25.4 ~ 152.4 mm (including liner 28.4 ~ 155.4 mm)	
		Width	25.4 ~ 115 mm (including liner 28.4 ~ 118 mm)	25.4 ~ 115 mm (including liner 28.4 ~ 118 mm)	
	Cutter Mode	Length	25.4 ~ 996 mm (including liner 28.4 ~ 999 mm) DT Mode: 35 ~ 996 mm (including liner 38~999mm)	25.4 ~ 996 mm (including liner 28.4 ~ 999 mm)	
		Width	25.4 ~ 115 mm (including liner 28.4 ~ 118 mm)	25.4 ~ 115 mm (including liner 28.4 ~ 118 mm)	
Ribbon	Length	Max: 300m (984')		N/A	
	Width	40 ~ 110 mm		N/A	
	Core Diameter	φ12.7mm (0.5"), φ25.4mm (1")		N/A	
	Wind Direction	Face-In/Face-Out, No Setting Change Required		N/A	

## FONTS & SYMBOLOGIES

Internal Fonts	Standard Bitmap	XS, XU, XM, XB, XL, OCR-A, OCR-B, Chinese (GB18030, Big5), Korean (KSX001)		
	Scalable Fonts	CG Times, CG Triumvirate™		
Barcode	Linear	Code 39, Code 93, Code 128, CODABAR(NW-7), EAN8/13, GS1 DataBar™, GS1-128(UCC/EAN128), Interleaved 2/5, Industrial 2/5, JAN8/13, Matrix 2/5, MSI, POSTNET™, UPC-A/E		
	2D Symbolologies	PDF417, Micro PDF, Maxi Code, GS1 Data Matrix, Data Matrix (ECC200), QR Code, Composite Symbolologies		

## INTERFACE CHARACTERISTICS AND INTEGRATION

Standard Interfaces	USB2.0 (Type B), Ethernet(IPv4/IPv6), RS232C(Standard Model Only)		
Optional Interface	Bluetooth 2.1		
External Memory	USB Type A (For Firmware Download)		
Remote Maintenance	SNMP Ver. 2		
Supported Printer Protocols	Standard: SBPL(SATO Barcode Printer Language) Emulation Language: SZPL, SEPL, SDPL, SIPL		
Drivers	Windows, Linux, Mac OS X, SAP Smart Forms		
OPTIONS	Cutter, Dispenser, Bluetooth, External Media Stand, Real Time Clock (Factory Option)		

## OPERATING & ENVIRONMENT CHARACTERISTICS

Electrical Requirements	Universal Auto-ranging Power Supply, 100-240VAC +/-10%, 50/60Hz		
Standards & Certifications	EN60950-1, UL60950-1/CSA C22.2 No. 60950-1, RCM, KC, EAC, S-Mark		
Agency Approvals	BIS, NOM, BSMI, KC, FCC, UL, CSA, CE, TUV GS, EAC, ICES-003, RCM, S-Mark, ROHS compliant, Cerner validated.		
Environment	Operating	5 to 40°C, 25-85% RH, Non Condensing	
	Storage	-20 to 60°C, 10-90% RH, Non Condensing	

## PHYSICAL CHARACTERISTICS

Dimensions	Width: 220.6mm (8.69"); Depth: 278.5mm (10.96"); Height: 187.5mm (7.38")	Width: 183.8mm (7.24"); Depth: 225.9mm (8.89"); Height: 166.0mm (6.54")
Weight	2.48kg (5.5lbs)	1.74kg (3.8lbs)

Scan QR code below for contact information:



Version: Mar 2024

Specifications subject to change without notice.

Any unauthorized reproduction of the contents of this presentation, in part or whole, is strictly prohibited. SATO is a registered trademark of SATO Holdings Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.